



WL3 Firewall®

Excellent purification performance
in an elegant and convenient dispenser

A sleek unit for anytime refreshment

The WL3 Firewall® (WL3 FW) by Waterlogic dispenses a choice of popular water types, including hot and extra hot options. Equipped with Firewall superior UVC purification technology, this unit guarantees you safe hydration and the best-tasting water.

Advanced technology

The WL3 FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense for microbiologically safe water. Tested effective against COVID-19 and guaranteed free from: up to 99.9999% bacteria, 99.99% viruses, and 99.9% cysts.



BioCote® product protection*

The WL3 FW key surfaces are infused with BioCote®, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.



Minimalist design and built for functional spaces

Built for the contemporary work environments where space is often a top priority, the WL3 FW is distinguished by its streamlined aesthetics and contained footprint (countertop model), making it an ideal complement to break areas, kitchenettes, and reception areas.

*BioCote® silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote® does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

Firewall-patented UVC technology reduces the risks of bacteria, viruses, and pathogens, purifying the water up to 99.9999%. Rigorously tested* and guaranteed effective at inactivating the human form of COVID-19 with a colony reduction of over 99.9999%

[Independently tested by the University of Arizona's Water & Energy Sustainable Technology (WEST) Center.]

Standard touch sensitive control panel for easy operations

Hands-free dispensing enabled by pedal controls

Dispensing area can accommodate average size reusable bottles

LED UV fault indicator for easier servicing and peace of mind

Energy-saving sleep mode reduces power consumption when the unit is not in use

Water options

cold sparkling ambient hot extra hot



Technical specifications

Types available

Tower and countertop

Dimensions (include feet)

Tower:

15.15" /385mm (W) x 44.88"/1140mm (H) x 14.37"/365mm (D)

Countertop:

15.15" /385mm (W) x 17.48" /444mm(H) x 17.77" /451.6mm (D)

Dispensing area height

9.25" /235mm

Weight

Tower: ~66-75 lbs/30-34 KG

Countertop: 59 lbs/27 KG

Recommended filtration

Carbon block (CBC) with lead, cyst, and asbestos reduction

Storage capacity

Cold tank (Tower): 4 liters (1.06 US gal.)

Cold tank (Countertop): 2 liters (0.53 US gal.)

Hot tank (Tower): 1.5 liters (0.4 US gal.)

Hot tank (Countertop): 1.5 liters (0.4 US gal.)

Compressor

120v 60Hz (R134a gas)

Water temperatures settings

Cold: 41°F/5°C

Hot : 183.2°F/84°C

Extra Hot : 199.4°F /93°C

Number of users 1 - 30

Contact us today

Waterlogic Commercial Products, LLC

Tel: 800-288-1891

waterlogicdealers.com

customerservice@waterlogicsusa.com

Tested and certified



Firewall technology is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.